


Under Decking Drainage

APPLICATION	52mm Drainage Cell
PROJECT LOCATION	Perth
PROJECT DETAILS	Under Decking Drainage
PROJECT COMPLETION	Oct 2010




Effective under Decking Drainage and Light Weight Durable Pedestal with 52mm Flo Cell.

To provide a drain under pavers, one simply lays a full layer of Atlantis[®] 52mm drainage cell clipped together on a slab and then simply sits the pavers on top thereof butted together. However if you wish to have a drain under wooden or the like floor boards, how do you do this both effectively and cost efficiently?

Why, with Atlantis[®] 52mm drainage cell, 30mm PVC pipes and tongue & groove hidden fasteners.

Atlantis[®] 52mm drainage cells are connected in a row across the edge of the area to be covered and additional spaced apart runs of Atlantis[®] 52mm drainage cells are connected at 90 degrees to the first row. A second row of Atlantis[®] 52mm drainage cells are connected across the ends of the runs and additional runs of Atlantis[®] 52mm drainage cells are connected to the second row in line with the first runs with a third row being connected to the ends of the additional runs so that the outer runs and outer rows extend to the perimeter of the area to be covered. The runs are spaced so that there is little or no give when people walk on the boards.



PVC piping is inserted along the length of each run and a tongue & groove hidden fastener is inserted into the groove of the floorboard above the PVC piping and is screwed into the PVC piping and then the next floorboard is pushed against the tongue and groove hidden fastener, where its tongue engages in the groove of the tongue and groove hidden fastener. This is repeated along every PVC piping for every floorboard.

With this arrangement it is not necessary to have the 52mm drainage cells cover the entire area and as the 52mm drainage cell forms part of the fastening means the cost are reduced and an effective solution is provided, with a long use life.



© Copyright 2016 Atlantis Corporation International Pty Ltd

ATLANTIS CORPORATION INTERNATIONAL PTY LTD

PHONE: + 612 9417 8344

FAX: + 612 9417 8311

EMAIL: info@atlantiscorp.com.au

WEB: www.atlantiscorp.com.au

NOTE: Atlantis products are manufactured from carefully selected high quality recycled materials. The strength of the recycled plastic could vary slightly due to raw material composition, country of manufacture, manufacturing process and external conditions. All trademarks are the property of Astral Property Pty Ltd. **DISCLAIMER:** All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. This information is intended only as a general guide, no responsibility can be accepted for any errors, omissions or incorrect assumption. As each project is unique, and as Atlantis Corporation Australia Pty Ltd and its distributors and agents world wide have no direct control over the methods employed by the user in specifying, installing or supervising of its products hence no responsibility is accepted by Atlantis Corporation Pty Ltd and its distributors and agents world wide. Users should satisfy themselves as to the suitability of the product for their purpose. All product designs, and specification are subject to change without further notice. All Atlantis products are tested in approved laboratories, and safe allowed tolerances should be practised in the actual field, to compensate for any unforeseen situations, on site and on products. **COPYRIGHT:** All material contained within this brochure is subject to copyright, and belongs to Atlantis Corporation Australia Pty Ltd. No part of this brochure may be reproduced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without prior written permission of Atlantis Corporation Australia Pty Ltd. Copyright @ 2016